



DIESEL FORKLIFT SERIES

Industrial Material Handling Equipment



WORLD PRIME SERVICES



DIESEL FORKLIFT - 1.5 T

Model CPCD-15 | Internal-combustion counterbalanced forklift



Compact 1.5-ton diesel forklift engineered for efficient loading, unloading and internal transport. The single-cylinder configuration combines durable mechanical construction with straightforward maintenance.

EFFICIENT POWER: Strong diesel output for stable lifting and material movement.

DURABLE CONSTRUCTION: Reinforced mast, overhead guard and solid industrial tyres.

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	SPECIFICATION
Engine model	-	Quandong Chai 1115
Rated power	HP	22
Total weight	kg	2200
Overall dimensions L x W x H	mm	2450 x 1360 x 2200
Wheelbase	mm	1350
Minimum turning radius	mm	2200
Rated lifting capacity	kg	1500
Load centre distance	mm	500
Standard lifting height	m	3
Front tyre	-	650-16



DIESEL FORKLIFT - 2.0 T

Model CPCD-20 | Internal-combustion counterbalanced forklift



A 2.0-ton single-cylinder diesel forklift developed for warehouses, yards and general industrial operations, offering reliable power delivery and a robust counterbalanced chassis.

STABLE HANDLING: Balanced chassis and reinforced mast for dependable operation.

SERVICE-FRIENDLY DESIGN: Simple mechanical systems and accessible engine compartment.

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	SPECIFICATION
Engine model	-	Quandong Chai 1115
Rated power	HP	22
Total weight	kg	2450
Overall dimensions L x W x H	mm	2900 x 1380 x 2200
Wheelbase	mm	1350
Minimum turning radius	mm	2400
Rated lifting capacity	kg	2000
Load centre distance	mm	500
Standard lifting height	m	3
Front tyre	-	650-16



DIESEL FORKLIFT - 3.0 T

Model CPCD-30 | Internal-combustion counterbalanced forklift



Industrial 3.0-ton diesel forklift with multiple engine options, a 3,000 mm standard lift and pneumatic-tyre configuration for demanding indoor and outdoor material handling.

ENGINE FLEXIBILITY: Euro 5, Mitsubishi S4S or Isuzu engine configurations.

INDUSTRIAL MOBILITY: Pneumatic tyres and controlled mast tilt for mixed-surface operation.

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	SPECIFICATION
Engine model	-	Euro 5 / Mitsubishi S4S / Isuzu
Rated load	kg	3000
Load centre distance	mm	500
Maximum lifting height	mm	3000
Wheelbase	mm	1770
Mast inclination	deg	6 / 12
Minimum turning radius	mm	2390
Maximum driving speed	km/h	18 / 19
Overall size L x W x H	mm	3913 x 1225 x 2160



DIESEL FORKLIFT - 3.5 T

Model CPCD-35 | Internal-combustion counterbalanced forklift



Heavy-duty 3.5-ton diesel forklift built for manufacturing, distribution and construction-material logistics, with a reinforced mast and selectable industrial diesel engines.

HEAVY-LOAD CAPABILITY: 3,500 kg rated capacity with a 500 mm load centre. **OPERATOR CONTROL:** Responsive steering, mast tilt and stable counterbalanced geometry.

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	SPECIFICATION
Engine model	-	Euro 5 / Mitsubishi S4S / Isuzu
Rated load	kg	3500
Load centre distance	mm	500
Maximum lifting height	mm	3000
Wheelbase	mm	1770
Mast inclination	deg	6 / 12
Minimum turning radius	mm	2390
Maximum driving speed	km/h	18 / 19
Overall size L x W x H	mm	3913 x 1225 x 2160